



PICTORIAL VIEW

Model ADD				
Size	A	B	C	D
12	12	13 1/8	14	14
18	18	19 1/8	20	14
24	24	25 3/4	27	18
27	27	28 3/4	30	18
30	30	31 3/4	33	18
34	34	35 3/4	37	18
36	36	37 7/8	39	18
42	42	43 9/16	45	18
48	48	49 5/8	51	18
60	60	61 5/8	63	24

- NOTES:
1. NON-SPARKING CAST ALUMINUM PROPELLERS
  2. WELDED CONSTRUCTION
  3. ANGLE IRON FLANGES
  4. PROTECTIVE COATING AVAILABLE
  5. ACCESS DOORS AVAILABLE
  6. OSHA FAN GUARDS AVAILABLE, 'D' DIMENSION MAY VARY IF REAR OSHA GUARD IS REQUIRED
  7. 0.44 INCH DIAMETER 8 HOLES EQUALLY SPACED ABOUT 'B' BOLT CIRCLE DIAMETER

DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE  
DRAWING NOT TO BE USED FOR CONSTRUCTION

		<b>CFM</b> Better Airflow By Design	
		TITLE: ADD DIRECT DRIVE TUBEAXIAL GENERAL SUBMITTAL DRAWING	
REV	DATE	BY: JWA	DATE: 06-JUN-2008   ADDGeneralModel.dft