

			1			1	
	Model#	Α	B	D	Ε	HP HP	G
	24	30	54x64	41 1/2	39	1/ 4- 1	25 1/2
	30	36	60x76	41 1/2	45	1/ 3- 1 1/ 2	25 1/2
	36	42	72x82	45 1/2	51	1/ 3- 2	27 1/2
	42	48	80x89	45 1/2	57	1/ 2- 3	27 1/2
	48	54	87x95	49 1/2	63	3/ 4- 5	29 1/2
	54	60	92x98	50 1/2	69	1- 5	29 1/2
Г	60	66	90x107	54 1/2	75	1- 10	31 1/2

NOTES

- (1) Fan can be supplied direct or belt drive.
- (2) Fan can be used for exhaust or supply.
- (3) Supply or exhaust fans can be supplied with shut off dampers. Dampers to be located in the curb, or fan mounting box.
- (4) Supply fan can be supplied with filters
- (5) Roof cap can be adapted to meet existing curb.
- (6) G & D Dimensions will vary with additional dampers, filter section, Explosion proof motors, etc.

☐ DIRECT DRIVE ☐ BELT DRIVE

Better Airflow By Design
HOODED ROOF VENTILATOR
HRV GENERAL SUBMITTAL

REV DATE BV J. E. EVANS | ITMAR 2008 | HRV GENERAL SUBMITTALdft

DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE.
DRAWING NOT TO BE USED FOR CONSTRUCTION.