


FLM FLEXIBLE INSULATED DUCT W/METALIZED VAPOR BARRIER

UL-181 and ULC S-110 M Class 1 Air Duct, wrapped with R4.2 insulation, 2-ply black polyester laminated inner core and an outer jacket made of fiberglass reinforced metalized film laminate. Suitable for use with various types of ventilation, heating and cooling systems.

	MODEL	A (INCHES)	LENGTH (FEET)
	FLM100	4"	10'
	FLM100-25	4"	25'
	FLM125	5"	25'
	FLM150	6"	25'
	FLM200	8"	25'
	FLM250	10"	25'
	FLM300	12"	25'

FEATURES & BENEFITS

- Available in 4" to 12" diameter
- Flexible galvanized steel wire helix
- R-Value: R-4.2
- 2-Ply black polyester inner core
- Fiberglass reinforced metalized outer jacket
- Maximum Flame Spread Index not over: 25
- Maximum Smoke Developed Index not over: 50

PERFORMANCE DATA

- Maximum air velocity 4000 fpm
- Maximum rated pressures:
 - Positive: 10 in. wg / intermittent; 6 in. wg / continuous
 - Negative: 2 in. wg
- Operating temperature range: 250 F (120 C) intermittent:
 - 2 in. wg: -20 to 180 F (-28 to 82 C)
 - 6 in. wg: -20 to 140 F (-28 to 60 C)

PROJECT		ARCHITECT	
DATE		ENGINEER	
SUBMITTED BY		CONTRACTOR	
SPECIFICATION			
MODEL NO.	LENGTH (FT)	QTY	OPTIONAL EQUIPMENT