



EXM External Mount Duct Fans offer the perfect solution when limited space prevents the use of an in-line duct fan. Access and maintenance are simplified with the through-the-wall design of an EXM fan that mounts on an exterior wall.

EXM EXTERNAL MOUNT DUCT FANS

Features & Benefits

- Steel housing with polymer coating
- Removable fan cover for easy maintenance
- · Sidewall mounted on the exterior of a building
- Quiet and efficient BC centrifugal motorized impeller
- External rotor motor design results in superior motor durability
- Suitable for air streams up to 113 F
- 120V, 60 Hz, single phase operation
- Permanently lubricated ball bearing motor for maintenance-free operation

PRODUGT

- Automatic reset thermal overload protection
- IP X4 protection
- Fits 4", 5", 6" & 8" duct
- · Airflow capacity to 306 cfm
- Two-year warranty

RESIDENTIAL & COMMERCIAL VENTILATION APPLICATIONS:

- Bathroom exhaustKitchen ventilation
- Crawl space ventilation
- Whole house ventilation
- GaragesOffice

- Warehouse
- Restaurant

			AIRFLOW PERFORMANCE (CFM)						
MODEL	WATTS*	RPM*	0" SP	0.25″ SP	0.5″ SP	1.0″ SP	1.5″ SP		
EXM100	108	3100	238	223	204	134	30		
EXM125	108	2950	248	231	213	146	25		
EXM150	109	2250	302	286	256	159	27		
EXM200	106	2300	306	291	258	148	9		

*RPM AND WATTS ARE INDICATED AT 0.2" SP

	DIMENSIONS IN INCHES*								
MODEL	DUCT DIA.	ØD	A	В	с	SHIP WT (lbs)			
EXM100	4″	3.9	14.0	10.3	5.4	9.0			
EXM125	5″	4.9	14.0	10.3	5.4	9.0			
EXM150	6″	5.9	15.8	11.8	5.4	9.9			
EXM200	8″	7.9	15.8	11.8	5.4	9.9			

*DO NOT USE FOR CONSTRUCTION

CONSULT FACTORY FOR CERTIFIED PRINTS

